DIGITAL PRESSURE GAUGE 2.5"

Pressure Range: 0 to 5000 psi

Temperature Compensation: -10 to +60°C Unit Selection: Psi, Bar, Mpa, Kg/cm² available

Zero Adjustment Weather Proof

The New-Flow DPG3500 Digital Pressure Gauge is designed to handle any applications by measuring air, liquid, and oil pressure. DPG3500 is using the most update temperature compensation technology, and the superior pressure meter equipped with variety of function such as unit selection, zero adjustment, and guarantee to long battery life, so it can be used for a variety of industrial and commercial applications without replacing battery for 3 years typical.



Power Supply: Lithium Battery CR123A (3.0V, 1400mAh)

Sampling Rate: 1.2 sec. max.

Battery Life: Without Back-Lighted: 3 Years for continuous operation;

Using Back-Lighted for 5secs (5 times per day): 1.5 Years for continuous operation

Pressure Range: 0~5000 PSI Pressure Unit: Psi, Bar, Kg/cm², Mpa Burst Pressure: 2 Time of F.S. Resolution: 1/1500 maximum Working Temperature: -10°C ~ +60°C Working Humidity: 35~85% RH Accuracy: ±1.0% F.S. (@25±3°C)

Port: Male thread 1/4"NPT, 1/4"PT (R1/4), 1/4"BSP, standard;

1/8"NPT, 1/8"PT (R1/8), 1/8"BSP available


Wetted Parts Material: SS316L


Measure Media: Gas and Liquid (compatible with wetted parts material SS316L)

Weather Proof: only for DPG3500-W

Weight: approx. 0.3 kg


Dimensions







(Weather Proof Type)



Dimensions Data

Thread	Α	В							
1/4"NPT	18 mm	8 mm							
1/4"PT (R1/4)	18 mm	8 mm							
1/4"BSP	18 mm	8 mm							
1/8"NPT	12 mm	8 mm							
1/8"PT (R1/8)	12 mm	8 mm							
1/8"BSP	12 mm	8 mm							

unit=mm



Ordering Information

DPG350	O Cod	de Type	Туре							
	W	Weat	Weather proof type General type							
	G	Gene								
		Cod	le Pressure	Pressure Range						
		1	15 psi	2	50 psi	3	100 psi	4	200 psi	
		5	300 psi	6	500 psi	7	1000 psi	8	3000 psi	
		9	5000 ps	isi						
			Code	Connecti	nnection Port					
	A 1/8"NPT male									
			В	B 1/8"PT (R1/8) male C 1/4"NPT male, standard D 1/4"PT (R1/4) male, standard E 1/8"BSP male						
			С							
			D							
			E							
			F	1/4"BSP male, standard						
	Code Power Supply									
				A Lithium Battery CR123A (3.0V, 1400mAh)						
\downarrow	Į	.								
DPG350	00		V		Complete Orde	ering Cod	le			