





Pressure sensors

CE Approved

PRE Series Range 1÷20 Bar - External use

Output	Case	Current output		Tension output			
		Code	Bar	Code	Bar	Code	Bar
 With solenoid connector DIN 43650 - ISO 4400	Stainless Steel-ABS	PRE53XXA..	*	PRE53XXC..	*	PRE53XXE..	*
	Brass - ABS	PRE03XXA..	*	PRE03XXC..	*	PRE03XXE..	*
 With Male Delphi connector	Stainless Steel-ABS	PRE51XXA..	*	PRE51XXC..	*	PRE51XXE..	*
	Brass - ABS	PRE01XXA..	*	PRE01XXC..	*	PRE01XXE..	*
 With cable type (1)	Stainless Steel-ABS	PRE52XXA..	*	PRE52XXC..	*	PRE52XXE..	*
	Ottone - ABS	PRE02XXA..	*	PRE02XXC..	*	PRE02XXE..	*
 With cable type (2)	Stainless Steel-ABS	PRE50XXA	*	PRE50XXC..	*	PRE50XXE..	*
	Brass	PRE00XXA..	*	PRE00XXC	*	PRE00XXE..	*


* Pressures available 1 - 2 - 5 - 10 - 20 bar

When ordering please specify the required pressure and cable type and length

Cable type (1) PVC (3 x 0,75) PRE models only

Cable type (2) Polyurethane (5 x 0,20 shielded with compensation hose)

PRS Series Range 0,5÷2 Bar - Submersible up to 2 Bar max. (20 m.)

Output	Case	Current output		Tension output			
		Code	Bar	Code	Bar	Code	Bar
 With cable	Stainless Steel	PRS50XXA..	0,5	PRS50XXC..	0,5	PRES50XXE..	0,5
			1		1		1
		2	2	2			
	Brass	PRS00XXA..	0,5	PRS00XXV..	0,5	PRS00XXE..	0,5
			1		1		1
		2	2	2			

When ordering please specify the required pressure and cable type and length

PVC 8 mm. cable (3 x 0,22 + compensation hose)

Polyurethane cable IMC (5 x 0,20 + screen and compensation hose)